



NetVanta 2050/2054

Small Office and Home Office VPN Gateway and Firewall

Product Features

- Standards-based IPSec VPN tunneling with DES/3DES/AES encryption
- Internet Key Exchange (IKE) for user authentication
- Stateful inspection firewall for network security
- Five private tunnels and up to 15 users
- Built-in IP router
- Network Address Translation for IP address concealing
- Web-based and CLI remote management
- 10/100Base-T Ethernet interfaces for flexible connectivity
- Logging and alerts
- Industry-leading five-year North American warranty



The ADTRAN NetVanta® 2050 and 2054 are Small Office/Home Office VPN/Firewall gateways providing all the necessary components required to secure an integrated VPN solution. Used primarily for remote access, the NetVanta 2050 and 2054 are perfect for work-at-home telecommuters needing to have a secure connection back to corporate resources. Based on the ADTRAN Operating System (OS), the NetVanta 2050 and 2054 provide key security and data protection features such as IPSec VPN tunneling, stateful inspection firewall, IP routing, Network Address Translation (NAT), and even a DHCP server. The 2050 and 2054 support the same features and perform the same functions, but the 2054 adds a built-in four-port 10/100Base-T Ethernet switch.

Security: On a public infrastructure like the Internet, security is of the utmost importance. The NetVanta 2050 and 2054 employs a stateful inspection firewall that protects an organization's network from common Denial of Service (DoS) attacks including TCP synflooding, IP spoofing, ICMP redirect, ping-of-death, and IP reassembly problems.

For the telecommuter that needs a dedicated firewall without corporate VPN access, the NetVanta 2050 and 2054 offer a firewall only version. The firewall only versions offer the same basic features, without IPSec VPN tunneling, encryption and authorization.

VPN Tunneling: The NetVanta 2050 and the 2054 are IPSec-compliant devices that provide secure communications over potentially unsecure networks. As security gateways, both the NetVanta 2050 and 2054 supports up to five simultaneous VPN tunnels and up

to 15 users on the LAN, while supporting encryption algorithms including DES, 3DES, and AES. In addition, these devices support IKE (Internet Key Exchange) and X.509 digital certificates for user authentication.

The firewall only versions of the 2050 and 2054 can be upgraded to support VPN with the purchase of the ADTRAN OS Enhanced Feature Pack upgrade. This feature pack is a firmware upgrade and adds all the VPN features mentioned.

Management: NetVanta's web-based GUI or CLI can be used for secure local or remote configuration of any NetVanta 2050 and 2054. N-Form®, ADTRAN's enterprise NMS, is ideal for managing larger NetVanta deployments and features a device manager, firmware manager and configuration manager to effectively manage a distributed NetVanta network. To administer user accounts, the NetVanta 2050 and 2054 utilizes XAUTH using RADIUS and RSA SecurID to manage administration account lists. These devices also offer built-in alert and logging mechanisms to warn administrators about activities that are going on in the network.

Interoperability: The NetVanta 2050 and 2054 offers the highest level of integration with ADTRAN's complete line of IPSec VPN equipped NetVanta products: NetVanta Ethernet Switches, NetVanta Access Routers, and NetVanta VPN/Firewall appliances. All of the ADTRAN internetworking products support the ADTRAN OS, ensuring common configuration practices and protection schemes between the various models. Together the NetVanta Series offers the most robust set of feature to address a wide range of enterprise VPN needs.



NetVanta 2050/2054

Small Office and Home Office VPN Gateway and Firewall

Product Specifications

Physical Interface

- **Public:** Auto-Sensing 10/100Base-T
- **Private:** 2050: One auto-sensing 10/100Base-T
2054: Four auto-sensing 10/100Base-T
- **Serial Port:** RS-232 for off-net configuration

Virtual Private Network (VPN)

Hash Algorithms

- MD5-HMAC 128-bit authentication algorithm
- SHA1-HMAC 160-bit authentication algorithm

Encryption

- DES-CBC (56-bit)
- 3DES-CBC (168-bit)
- AES (128-bit, 192-bit, 256-bit)

Diffie Hellman Group Support

- **Group 1:** MODP 768
- **Group 2:** MODP 1024

Authentication Mechanisms

- Preshared keys
- X.509 Certificate Support: RSA Signatures, DSS Signatures

Key Management

- IKE (ISAKMP/Oakley)

IPSec Mode

- Tunnel

IKE

- Modes: Main, Aggressive, and Perfect Forward Secrecy
- XAUTH
- Mode Config

Firewall

- Stateful inspection firewall
- Denial of Service (DoS)

Diagnostics

Front Panel Status LEDs

- **Power:** status
- **VPN:** status, transmit, receive
- **Private:** transmit, receive
- **Public:** transmit, receive

Routing

- IP
- OSPF, RIP, and Static Routes

Network Address Translation

- Basic NAT (1:1)
- NAT (Many:1)
- Reverse NAT (translation of an inbound session's destination IP address)
- Application Level Gateways for FTP, HTTP, POP3, SIP, H.323, and others

Administration

- Web-based graphical interface
- Command Line Interface (CLI)
- N-Form support
- SYSLOG logging in WELF format
- Email alerts (SMTP)

DHCP

- Server (to manage IP addresses on local network)
- Client (to acquire IP address from service provider)
- MAC Address Masquerading

PPPoE

- Client (to acquire IP address from service provider)

Environment

Operating Temperature

- 0° to 50°C (32° to 122°F)

Storage Temperature

- -20° to 70°C (-4° to 158°F)

Relative Humidity

- Up to 95%, non-condensing

Physical

Size: 1.625" H, 7.5" W, 5.437" D

Weight: 2 lbs. (shipping weight)

Power: 12 VDC Power, 4 W

Agency Approvals


- FCC Part 15 (Class B)
- UL and Canadian UL (CUL), IEC/EN, CSA, CE Mark

Product Includes


- 12 VDC locking power supply
- 6 ft. crossover Ethernet cable
- User manual ■ Quick start guide

Ordering Information

Equipment	Part #
NetVanta 2050	1202362L2
NetVanta 2050 Firewall	1202362L1
NetVanta 2054	1202363L2
NetVanta 2054 Firewall	1202363L1
NetVanta 2000 Series VPN Upgrade	1950362L2



NetVanta 2050



NetVanta 2054

ADTRAN, Inc.
Attn: Enterprise Networks
901 Explorer Boulevard
Huntsville, AL 35806

P.O. Box 140000
Huntsville, AL 35814-4000

256 963-8000 voice
256 963-8699 fax

General Information
800 9ADTRAN
info@adtran.com
www.adtran.com

Pre-Sales

Technical Support

800 615-1176 toll-free
application.engineer@adtran.com
www.adtran.com/support

Where to Buy

877 280-8416 toll-free
channel.sales@adtran.com
www.adtran.com/where2buy

Post-Sales

Technical Support

888 423-8726
support@adtran.com
www.adtran.com/support

ACES Installation & Maintenance Service

888 874-ACES
aces@adtran.com
www.adtran.com/support

International Inquiries

256 963 8000 voice
256 963-6300 fax
international@adtran.com
www.adtran.com/international

For the regional office nearest you, visit:

www.adtran.com/where2buy



ADTRAN is an
ISO 9001:2000 certified supplier.



ADTRAN is a
TL 9000 3.0 certified supplier.

61202362L2-8D May 2004
Copyright © 2004 ADTRAN, Inc.
All rights reserved.

Specifications subject to change without notice. ADTRAN, N-Form, and NetVanta are registered trademarks of ADTRAN, Inc. All other registered trademarks and trademarks mentioned in this publication are the property of their respective owners.